

SALES & SERVICE NETWORK



	Manufacturing Unit
	Head Office
	Regional Office
	Branch office
	Dealers
	Spares Depot
	Training Center
	Sales Executive
	Service Engineers
Branch Offices	
	Ahmedabad
	Bangalore
	Ghaziabad
	Hyderabad
	Indore
	Kolkata
	Mumbai
	SERVICE / SUPPORT / SPARES +91 - 7878740000



Concrete Batching Plant
(INFRA Series)



Concrete Batching Plant
(RMC Series)




Mobile Batching Plant




Deep Bucket Batching Plant



Tora Batching Plant



Self Loading Mixer



Stationary Concrete Pump



Concrete Canal Paver



Concrete Road Paver



Concrete Mixer

CONMAT HEAVY INDUSTRIES PVT. LTD.

Formerly Known as KYB Conmat Pvt. Ltd.

702-703, N.H. No. 8, Por,
Dist - Vadodara - 391243, Gujarat, INDIA
Ph.: +91-265 - 6132900, 3000300
Email:sales@conmatindia.com
www.conmatindia.com

ISO Certified :- 9001:2015, 27001:2022 & 45001:2018

CIN: U29248GJ2007PTC052387

Note: The technical specifications of the product may vary depending on the model and are subject to change without prior notice.

Follow us on :



MKT/PC/6.03/06 R2 Aug25



Self Loading Concrete Mixer



ARAI Approved





A	1455
B	2150
C	1270
D	5665
E	1350
F	2945
G	330
H	3670
I	2420
J	32°

All Dimensions in mm

Sr.	Details	
1	Drum Output per batch	2.5 Cu.M
2	Drum Rotation	0-22 RPM
3	Bucket Capacity	420 Ltr.
4	Vehicle Speed	0-22 Kmph
5	Braking system	Hydraulic powered brakes
6	Engine	KOEL 4R810T BS-V Diesel Engine 4 Cylinder Turbocharged, Water Cooled 49 HP @ 2200 RPM BS-V Emission Compliant
7	Gradeability	20 Deg / 36.4%
8	Weighing Technology	Pressure Transducer

Sr.	Details	
9	Tyre & Rim	12.5/80x18, 16 PR
10	Fuel Tank	100 Ltr.
11	Hydraulic Tank	112 Ltr.
12	Water Tank	500 Ltr.
13	Water Pump Capacity	230 Lpm.
14	Chassis	Box Type
15	Net Vehicle Weight	6500 KG. Approx
16	Laden Weight	12500 KG. Approx
17	Drive	Full Time 4 Wheel Drive
18	Wheel base	2150




A	1590
B	2650
C	1556
D	6890
E	1610
F	3160
G	370
H	4195
I	2480
J	33°

All Dimensions in mm


Sr.	Details	
1	Drum Output per batch	4.3 Cu.M.
2	Drum Rotation	0-22 RPM
3	Bucket Capacity	600 Ltr.
4	Vehicle Speed	0-28 Kmph
5	Braking system	Hydraulic powered brakes
6	Engine	KOEL 4R1190TA1 BS-V Engine 4 Cylinder Turbocharged, Inter- Cooled 110 HP/81 Kw @ 2200 RPM BS-V Emission Compliant
7	Gradeability	25.5 Deg/47.5%
8	Weighing Technology	Pressure Transducer

Sr.	Details	
9	Tyre & Rim	16.0/70x20, 14 PR
10	Fuel Tank	120 Ltr.
11	Hydraulic Tank	112 Ltr.
12	Water Tank	900 Ltr.
13	Water Pump Capacity	360 Lpm.
14	Chassis	Box Type
15	Net Vehicle Weight	8100 Kg. Approx
16	Laden Weight	18420 KG. Approx
17	Drive	Full Time 4 Wheel Drive
18	Wheel base	2650



A	1455
B	2350
C	1270
D	5885
E	1400
F	2945
G	300
H	3670
I	2450
J	32°

All Dimensions in mm



A	1780
B	2750
C	1420
D	7095
E	1610
F	3210
G	370
H	4230
I	2480
J	30°

All Dimensions in mm



Sr.	Details	
1	Drum Output per batch	2.8 Cu.M.
2	Drum Rotation	0-22 RPM
3	Bucket Capacity	420 Ltr.
4	Vehicle Speed	0-25 Kmph
5	Braking system	Hydraulic powered brakes
6	Engine	KOEL 4R1190NA1 BS-V Diesel Engine 4 Cylinder Water Cooled 74.5 HP @ 2200 RPM BS-V Emission Compliant
7	Gradeability	20 Deg / 36.4%
8	Weighing Technology	Pressure Transducer



Sr.	Details	
9	Tyre & Rim	12.5/80x18, 16 PR
10	Fuel Tank	100 Ltr.
11	Hydraulic Tank	112 Ltr.
12	Water Tank	625 Ltr.
13	Water Pump Capacity	230 Lpm.
14	Chassis	Box Type
15	Net Vehicle Weight	6900 Kg. Approx
16	Laden Weight	13620 KG. Approx
17	Drive	Full Time 4 Wheel Drive
18	Wheel base	2350



Sr.	Details	
1	Drum Output per batch	4.8 Cu.M.
2	Drum Rotation	0-22 RPM
3	Bucket Capacity	700 Ltr.
4	Vehicle Speed	0-28 Kmph
5	Braking system	Hydraulic powered brakes
6	Engine	KOEL 4R1190TA1 BS-V Diesel Engine 4 Cylinder Turbocharged, Inter Cooled 110 HP/81 Kw @ 2200 BS-V Emission Compliant
7	Gradeability	24.5 Deg / 45.5%
8	Weighing Technology	Pressure Transducer

Sr.	Details	
9	Tyre & Rim	16.0/70x20, 14PR
10	Fuel Tank	120 Ltr.
11	Hydraulic Tank	112 Ltr.
12	Water Tank	1000 Ltr.
13	Water Pump Capacity	360 Lpm.
14	Chassis	Box Type
15	Net Vehicle Weight	7690 Kg. Approx
16	Laden Weight	19210 KG. Approx
17	Drive	Full Time 4 Wheel Drive
18	Wheel base	2750

Note: The technical specifications of the product may vary depending on the model and are subject to change without prior notice




A	1695
B	2650
C	1400
D	6940
E	1610
F	3200
G	370
H	4130
I	2410
J	29°

All Dimensions in mm

Sr.	Details	
1	Drum Output per batch	4.2 Cu.M
2	Drum Rotation	0-20 RPM
3	Bucket Capacity	600 Ltr.
4	Vehicle Speed	0-22 Kmph
5	Braking system	Hydraulic powered brakes
6	Engine	KOEL 4R1190NA1 BS-V Diesel Engine 4 Cylinder Water Cooled 74.5 HP @ 2200 RPM BS-V Emission Compliant
7	Gradeability	20 Deg / 36.4%
8	Weighing Technology	Pressure Transducer

Sr.	Details	
9	Tyre & Rim	16.0/70x20, 14 PR
10	Fuel Tank	120 Ltr.
11	Hydraulic Tank	112 Ltr.
12	Water Tank	900 Ltr.
13	Water Pump Capacity	230 Lpm.
14	Chassis	Box Type
15	Net Vehicle Weight	7700 Kg. Approx
16	Laden Weight	17780 KG. Approx
17	Drive	Full Time 4 Wheel Drive
18	Wheel base	2650



Steering System



Short turning radius



Electronic batch controller

Salient Features

- Specially designed blades for better mixing & faster discharge
- Powered Shovel gate for spillage free charging
- Loading arms mechanism designed for better pushing force & ease of operation while loading
- Single Joystick for all main functions
- Low centre of gravity
- Specially designed blades for better mixing & faster discharge
- Electronic weigh batching system with printer
- Reversible operator post for better visibility
- Four wheel steering systems, with 3 different modes ideal for working in confined spaces
- Short turning radius
- Live tracking & monitoring system
- Admixture System (optional)
- Cold Starting Kit (optional)
- Rear View Camera (optional)
- ROPS / FOPS Cabin (optional)