



Concrete Paving Machine



THE MOST ADVANCED & USER FRIENDLY CONCRETE PAVING MACHINE



- **Low power consumption with higher output, hence faster payback**
- **Remote operator controls for better monitoring while paving**
- **Advanced energy efficient electric drive system with step less speed control**
- **User-Friendly, Fast & accurate controls**



Groove Cutter
(Optional)




PVC Water Stop Attach
(Optional)



Extra Long Paving
(Hardened Auger)

Conmat manufactures exclusive range of standard and customized high performance Paving Machines for slopes well as horizontal surfaces. These world class products are characterized by high efficiency, reliability, as well as solidity. Our dedicated team of engineers ensure excellent support right from installation to commissioning and after sales service.

Data & Facts



Prime Mover

- 5 HP Geared Motor - Driver End Panel
- 5 HP Geared Motor - Vibratory Cylinder
- 1 HP + 1 HP Geared Motor - Bogie RH & LH
- 1 HP Electric Motor - Vibratory Cylinder

Traction System

- Traction Drive: Two Electrically driven double flanged bogie wheels
- Traction Speed : 0-5 mpm

Vibratory Cylinder Under Carriage

- Finished Cylinder 270 mm dia., 1.2 mtr. long precisely balanced
- Extra Long Screw Auger(RH&LH) with hardened flights
- Finishing Tolerance: ± 3 mm in 12ft.

Machine Controls

- Adjustable Carriage Movement with Variable Speed Drive
- Shock Protection
- Overload Protection

Construction

- Frame: All welded, pin connected main frame. Available in length of 2.40 mtr., 1.2 mtr., 0.6 mtr., which are infinitely adjustable up to 62 ft.(CE200) and 110 ft (CE 200 HD/CE 400)
- Finishing Width: Finishing width normally 3ft.(0.9 mtr.) less than frame width and adjustable from 1mtr. to 32mtr.
- Also available for large depth upto 450mm thick slab, span upto 62ft. long adjustable (CE200F) with optional needle/pan vibrator

Optional

- Longitudinal & Transverse Groove Marker
- Longitudinal & Transverse PVC Water Stop inserter Attachment
- Trimmer Attachment
- Transport Assembly
- Slope Wedges
- ◆ FIX FORM concrete paver fitted with Gang Vibrators, is an economical alternative to slip form paver for city and road projects



Gang Vibrator




Needle Vibrator
(Optional)



PAN Vibrator
(Optional)

Paves Half Width, Trapezoidal Canals, & Straight side slopes up to 45 degree angle. • Rated output 18-20 cu.mtr./hr under ideal conditions and application • Inbuilt vibratory cylinder attachment for better compaction • Optimum use of power for improved overall efficiency of the machine.

SALES & SERVICE NETWORK



	Manufacturing Unit
	Head Office
	Regional Office
	Branch office
	Dealers
	Spares Depot
	Training Center
	Sales Executive
	Service Engineers
Branch Offices	
<ul style="list-style-type: none"> ● Ahmedabad ● Hyderabad ● Udaipur ● Indore ● Mumbai ● Bangalore ● Ghaziabad ● Kolkata 	<ul style="list-style-type: none"> ● Hyderabad ● Ahmedabad ● Udaipur ● Indore ● Mumbai ● Bangalore ● Ghaziabad ● Kolkata
 SERVICE / SUPPORT / SPARES +91 - 7878740000	



Works : Vadodara - Gujarat



Concrete Batching Plant
(INFRA Series)



Concrete Batching Plant
(RMC Series)



Mobile Batching Plant



Deep Bucket Batching Plant



Tora Batching Plant



Self Loading Mixer



Stationary Concrete Pump



Concrete Canal Paver



Concrete Road Paver



Concrete Mixer

CONMAT HEAVY INDUSTRIES PVT. LTD.

Formerly Known as KYB Conmat Pvt. Ltd.

702-703, N.H. No. 8, Por,

Dist - Vadodara - 391243, Gujarat, INDIA

Ph.: +91-265 - 6132900, 3000300

Email:sales@conmatindia.com

www.conmatindia.com

ISO Certified :- 9001:2015, 27001:2022 & 45001:2018

CIN: U29248GJ2007PTC052387



Follow us on :